

Ticketing Series

60mm ticket printer

Industrial Components



Vertical 60 mm ticket printer to integrate into kiosks and information points, industrial solutions and precision machinery.

Its compact size, higher printing speed, resolution as well as its 60 mm auto-cut presenter make the NP-2511 a very competitive ticketing printer for vertical mounting installations.

Prints with 16 gray scale gradation.



TECHNICAL SPECIFICATIONS

OTHER TECHNICAL DATA

I/O PORTS

**Direct Importer:** Grupo EOS Ibérica

**Interface:** Dual Serial (RS232C) and USB 2.0.  
**Operating voltage:** DC 24V.  
**External dimensions:** 75(H) x 106(W) x 150(D)mm  
**Weight:** Approximately 650 g.

**Options:**  
**Power supply:** YS-48.  
**Bezel:** BEZ-220, BEZ-221 (with paper detection sensor) BEZ-320 (with blue or red LED).  
**Large paper roll holder:** UPH-LA.

**GENERAL INFORMATION:**

**Operating temperature:** -20°C to +60°C.  
**Paper thickness:** 65 - 150 microns.  
**Printing method:** Direct thermal.  
**Print speed:** max. 200mm/s.  
**Number of printing dots (dots):** 576.  
**Paper width:** 58/60 adjustable  
**Print Width:** 52mm (Default), 56mm  
**Paper roll diameter:** 83mm.  
**Paper roll thickness:** 65-150 µm.  
**Cutting method:** Total and partial cutting (selectable command).  
**Print head life:** 100 km.  
**Bar-code:**  
 UPC-A, UPC-E, EAN(JAN-13), EAN(JAN-8), CODE39, ITF, CODABAR, CODE128, QR code (model 2) / PDF417.



Front



Rear

BEZEL OPTIONS



BEZ-220/221/230/231



NPT-306



UPH-LA

**MOST COMMON APPLICATIONS**

- > Banking applications.
- > Sports betting.
- > Parking.
- > Gas stations.
- > Retail.
- > Transportation.
- > Vending.

**PRODUCT VALUES**

- > Compact format.
- > Robust, reliable design.
- > Head opening for easy handling.
- > 16 gray scale.
- > 2D barcode.

**SOME SUCCESS STORIES**

- > Kiosks for shift management.
- > Unattended kiosks.

**ALTERNATIVE REFERENCES**

- > e80 NP3411
- > e80 MS-V

CERTIFICATIONS



CONNECTIONS

DIMENSIONS

DIMENSIONS

