INTERACTIVE KIOSK

n eosibérica

Outdoor Kiosk Series

Terminal de exterior de doble pantalla

Customisable / Outdoor



Square communication. Terminal designed to incorporate a large screen on both sides of the structure. This allows for a greater visual impact on customers or to speed up user interaction with the kiosk.

The monocogue structure has a double sealed base and forced ventilation. It can be manufactured in AISI 304 stainless steel, 316 for marine environments or 316L for corrosive environments. Designed under the IP65 standard to incorporate peripherals that support this degree of protection.

In addition, peripherals such as webcam, receipt printer, card reader or DNIe can be integrated, adapting to the needs of each project. It is available in any colour from the RAL range and can be adapted to the customer's brand image by means of cut vinyl or digital image.



Manufacturer: Grupo EOS Ibérica Origin: Manufactured and assembled in Spain.

Production:

> 4 weeks (estimated time).

Material:

> 2 / 5 mm carbon steel sheet.

Flanges/Interior fastenings:

> Galvanised sheet metal.

> High resistance epoxy paint.

Watertightness and sealing:

> IP65.

Dimensions 2300x945x400 mm

Structural weight:

150Kg

> Outdoor

STANDARD SPECIFICATIONS

> Industrial LCD 24/7 High luminance(*)

Screen resolution:

> 22", 4:3 (horizontal).

Number of screens:

Video output:

> HDMI, DVI, SVGA,

Screen protection:

> Antivandal glass 3+3 mm.

Accesses:

> 1 rear door with three-point security lock.

Electrical panel:

> Terminal, circuit breaker and differential.

> Power supplies 5/12/24v.

Colour of structure :

> RAL: White 9003

(*)The sun must not shine directly on the screen.

OPTIONAL COMPONENTS

Touch screen:

> IR 3mm or capacitive 6mm technology. Fanless Industrial PC:

> Atom /Celeron/ i3/ i5/ i7.

Operating System:

> Android, Windows or Linux

Multimedia:

> Speakers.

> WebCam

External Connections:

> WiFi Antenna.

Uninterruptible Power Supply:

> 6-socket UPS.

Personalisation/Customisation:

> Cut vinyl/digital image.

> Airbrushing or multicolour Graffiti.

> Industrial painting in various Colours RAL.

Screen resolution:

> 17", 19" 21,5", 43" 49"

Screen layout:

> Horizontal or vertical (please consult). Ticketing:

> 60 mm o 80 mm ticket printer. Readers:

> Barcode / QR

> DNIe.

Ingenico, Verifone, Hypercom POS module:

> Card reader + PinPad + Contactless.

Cooling system:

> Advertising

> Directory.

> Smartcity.

> Digital Signage

> Interactive map

> Forced ventilation

> Intelligent AA system.

Customised side with fretwork:

> With or without led backlighting.

MOST COMMON APPLICATIONS

PRODUCT VALUES


- > Robust
- > Watertight for outdoors
- > Vandal-proof.
- > Accessibility.
- > Great communication power.
- > Speed.

ALTERNATIVE REFERENCES

- eTótem Xtrem Dual Side
- > eTótem Xtrem >eTótem.

PRODUCT SIZES AND PRODUCT VERSIONS

858 911 1007




MOST COMMON SECTORS

- > Communication, advertising and marketing
- > Public administrations.
- > Tourism.
- > Sports and leisure.
- > Queue management.
- > Museums and libraries. > Industry.
- > Train, metro and bus stations.

SUCCESS STORIES





SUCCESS STORIES



