

Panel PC Serie

Fanless Industrial Computers

Industrial Components



Elevation

15" INTEL I5 1.60ghz - 3.90ghz Industrial Touch Panel PC with 8th generation 8265u processor.

15" touch screen monitor with capacitive technology and fanless ruggedised computer in aluminium chassis in grey colour, with passive cooling system without using fans.

HDMI video output for connection of 1 external monitor. 4 USB ports (4 x 3.0). Includes TPM 2.0 security. VESA mounting system or panel mountable using supplied brackets. Wide voltage range 9-36V.



Indoor

TECHNICAL SPECIFICATIONS

OTHER TECHNICAL DATA

PORTS I/O

Direct Importer: Grupo EOS Ibérica SA

Processor: Intel i5 8265U 1,60Ghz base
Resolution: 1280x800 (Native). 350 cd/m2
RAM: Supports up to 16GB SODIMM DDR4
ROM: SSD SATA / SSD M.2 2280 / HDD SATA
Audio: 2x Jack 2.5; Speakers / MIC
Socket: 1x RAM / 1x SATA / 1x MiniPCIE / 1x M.2
Ports: 4xUSB 3.0 / 1xHDMI / 2x RS232 (COM2 supports RS422/485)
LAN: 2xRJ45
OS: Windows 7, 8, 10, 11. Linux Compatible
Power supply: DC100-240V AC input / DC12v/6A output
Power consumption: ~ 35-65 watts
Vibration: Vibration resistant
Humidity: 5% ~ 95% (non-condensing)
Operating temp.: 0°C~50°C
Storage temp.: -20°C~60°C
Warranty: 1 Year (Extendable up to 3 years)

Mounting Type: Panel mountable yes, VESA yes, RACK no.

Processor Frequency: Minimum 1.60Ghz, maximum 3.90Ghz
Graphics: Intel® UHD Graphics for 8th Generation Intel® Processors
RAM: 0 Gb on Board + 1 Socket SODIMM DDR4 (4/8/16Gb)
ROM: SSD 2.5/ SSD M.2 SATA (240Gb, 480Gb) / HDD 2.5 (500Gb, 1Tb) *Consult other capacities
Audio: Realtek HD ALC662 Line-out and MIC
LAN: Realtek RTL8111F or Intel I210/I211 AT 10/100/1000Mbps. Wake on Lan
IP Protection Display: IP65 front. Water jetted (from any angle) through a 6.3 mm diameter nozzle must not enter, provided the panel mounting is correct
IP Protection Pc Industrial: IP50. Dust ingress cannot be prevented, but must not enter in such a quantity as to interfere with the correct operation of the equipment
Wireless: Mini PCI Express Intel 7260BN. WiFi 802.11 b/g/n (OPTIONAL)
GPS: Mini PCI Express u-Blox pci-5s-1 - 500
3G/GPS: Mini PCI Express Huawei EM770w. (OPTIONAL)
4G/GPS: Mini PCI Express Huawei ME909u-521. (OPTIONAL)
Dimensions: 271.5 * 190 * 53 mm (LxWxH)
Weight: 2 Kg
Packing: Single Box; PC, Power Supply, Power Cable, Drivers



CONNECTIVITY OPTIONS

PRODUCT VALUES

- > Quality capacitive touch.
- > 15.6" monitor + Dual video output.
- > Resistant to aggressive environments; dust, grease, vibrations.
- > Resistant to extreme temperatures and humidity.
- > Expandable equipment in its configuration, up to 8gb of RAM memory.
- > Possibility of Wifi or 4G / GPS connection.
- > Very low power consumption.

WiFi module: Intel 7260BN
WiFi antenna: Yes
Connection cable: Yes
SMA extender: Optional



4G/GPS module: ME909u-521
4G/GPS antennas: Yes
Connection cable: Yes

MOST COMMON APPLICATIONS

- > HMI control panels
- > Integration in electrical panels
- > Industrial control systems (ICS)
- > Distributed control systems / SCADA
- > Data Acquisition Systems (DAQs)
- > Data Acquisition Systems (DAQs)
- > Factory assembly lines
- > Assembly in transport vehicles
- > Wireless station (Wifi/4G/GPS)
- > Outdoor advertising and digital signage.
- > Interactive kiosks, multimedia
- > Self-pay kiosks, unattended kiosks

APPLICATION SECTORS

- > Agricultural engineering
- > Meat industry
- > Automation
- > Aerospace
- > Automotive
- > Data Centers
- > Distribution
- > Marine
- > Pharmaceutical Industry
- > Transport and Logistics
- > Transmission applications

SIDE OR VESA MOUNTING SYSTEM



SUCCESS STORIES

- > Interactive kiosks
- > Factory-floor assembly
- > Solutions for agricultural engineering

ALTERNATIVE REFERENCES

- > Panel Pc industrial 15" ePX15 i5-4200u
- > Panel Pc industrial 17" ePX17 i5-4200u
- > IR 17" touch screen + industrial pc

CERTIFICATIONS



CONNECTIONS



DIMENSIONS

