




Elevation

15.6" INTEL i5 1.90GHZ Industrial Touch Panel PC with 4th generation 4300u processor.

15.6" touch screen monitor with capacitive technology and fanless ruggedised computer in black aluminium chassis, with passive cooling system without the use of fans.

It has double HDMI and VGA video output for the connection of 1 external monitor that with its own screen makes it possible to work with 2 screens at the same time. 4 USB ports (1 x 3.0 and 3 x 2.0). VESA mounting system or panel mountable with the use of supplied brackets.



Indoor

TECHNICAL SPECIFICATIONS

Direct Importer: Grupo EOS Ibérica SA

- Processor:** Intel I5 4300U 1,90Ghz
- Resolution:** 1366x768 (Native)
- RAM:** Supports up to 8GB SODIMM DDR3/2800
- ROM:** SSD SATA / SSD MSATA / HDD SATA
- Audio:** 2x Jack 2.5; Speakers / MIC
- Socket:** 1x RAM / 1x SATA / 1x MiniPCIE / 1x mSATA
- Ports:** 1xUSB 3.0 / 3xUSB 2.0 / 1xHDMI/ 1xVGA/ 2 RS232 (COM2 supports RS422/485).
- LAN:** 1xRJ45
- OS:** Windows 7, 8, 10, Linux Compatible
- Power supply:** DC100-240V AC input / DC12v/6A output
- Power consumption:** ~ 35-65 watts
- Vibration:** Vibration resistant
- Humidity:** 5% ~ 90% (non-condensing)
- Operating temp.:** -10°C~60°C
- Storage Temp.:** -20°C~70°C
- Warranty:** 1 Year (Extendable up to 3 years)

OTHER TECHNICAL DATA

- Type of anchorage:** Panelable yes, VESA yes, RACK no.
- Processor Frequency:** Minimum 1.90Ghz, maximum 2.90Ghz.
- Graphics:** Integrated Intel HD 4400 Series. LVDS, Dual HDMI/ VGA output.
- RAM:** 0 Gb on Board + 1 Socket SODIMM/1,35v (4/8Gb)
- ROM:** SATA SSD / MSATA SSD (120, 240Gb) / SATA HDD (500Gb, 1Tb) * Consult other capacities.
- Audio:** Realtek HD ALC662 Line-out and MIC
- LAN:** Realtek RTL8111F or Intel I210/I211 AT 10/100/1000Mbps. Wake on Lan.
- IP Protection Display:** IP65 front. Water jetted (from any angle) through a 6.3 mm diameter nozzle will not enter, provided the panel mounting is correct.
- IP Protection Pc Industrial:** IP50. Dust ingress cannot be prevented, but must not enter in such a quantity as to interfere with the correct operation of the equipment.
- Wireless:** Mini PCI Express Intel 7260BN. WiFi 802.11 b/g/n (OPTIONAL)
- GPS:** Mini PCI Express u-Blox pci-5s-1 - 500
- 3G/GPS:** Mini PCI Express Huawei EM770w. (OPTIONAL)
- 4G/GPS:** Mini PCI Express Huawei ME909u-521. (OPTIONAL)
- Dimensions:** 397 x 246 x 44 mm (LxWxH)
- Weight:** 3'25 Kg
- Packing:** Single Box; PC, Power Supply, Power Cable, Drivers.

PORTS I/O



CONNECTIVITY OPTIONS

- WiFi module:** Intel 7260BN
- WiFi antenna:** Yes
- Connection cable:** Yes
- SMA extender:** Optional
- 4G/GPS module:** ME909u-521
- 4G/GPS antennas:** Yes
- Connection cable:** Yes

SIDE OR VESA MOUNTING SYSTEM



PRODUCT VALUES

- > Quality capacitive touch.
- > 15.6" monitor + Dual video output.
- > Resistant to aggressive environments; dust, grease, vibrations.
- > Resistant to extreme temperatures and humidity.
- > Expandable equipment in its configuration, up to 8gb of RAM memory.
- > Possibility of Wifi or 4G / GPS connection.
- > Very low power consumption.

MOST COMMON APPLICATIONS

- > HMI control panels
- > Integration in electrical panels
- > Industrial control systems / SCADA
- > Distributed control systems / SCADA
- > Data Acquisition Systems (DAQs)
- > Data Acquisition Systems (DAQs)
- > Factory assembly lines
- > Assembly in transport vehicles
- > Wireless station (Wifi/4G/GPS)
- > Outdoor advertising and digital signage.
- > Interactive kiosks, multimedia
- > Self-pay kiosks, unattended kiosks

APPLICATION SECTORS

- > Agricultural engineering
- > Meat industry
- > Automation
- > Aerospace
- > Automotive
- > Data Centers
- > Distribution
- > Marine
- > Pharmaceutical Industry
- > Transport and Logistics
- > Transmission applications

SUCCESS STORIES

- > Interactive kiosks
- > Factory-floor assembly
- > Solutions for agricultural engineering

ALTERNATIVE REFERENCES

- > Panel Pc industrial 15" ePX15 i5-4200u
- > Panel Pc industrial 17" ePX17 i5-4200u
- > IR 17" touch screen + industrial pc

CERTIFICATIONS



CONNECTIONS



DIMENSIONS

