# eSanitizer

## **Medical Serie**



PRODUCT PROFILE

PRODUCT VALUES

Origin: Manufactured and assembled in Spain.

Manufacturer: Grupo EOS Ibérica

> 4 weeks (estimated time).

Flanges/Interior fastenings:

> High resistance epoxy paint.

Watertightness and sealing:

Dimensions: > 800x550x110 mm

> Galvanised sheet metal.

> 1.5 / 5 mm carbon steel sheet.

Production:

Material:

Finish:

20Kg.

Use:

vinyl

> eDispenser > eTótem Sanitizer

> Indoor.

> IP65 (optional).

800x550x110 mm

Structure weight:

> Safety and security

> Hand disinfection.

> To hang on any wall.

> Prevention of contagion

> Vandal-proof protection.

> Viability of installation in small spaces

> Easy to personalise with digital image or cut

ALTERNATIVE REFERENCES

# INFORMATION AND SECURITY TERMINAL

## Wall terminal for hand disinfection

D)eosibérica

# Customisable / Indoor

AUTOMATIC GEL DISPENSER WITH DISPLAY. The eSanitizer allows you to disinfect your hands before touching the screen or entering an establishment.

The touch-free dispenser has a sensor that detects the user's hand and pours the required dose of gel. It can incorporate a 19" touch screen or a thermal camera with facial recognition for fever detection.

It has a front-opening door, allowing easy maintenance of the terminal, such as refilling with hydroalcoholic gel. In the hall, at the reception or at the entrance control. To identify yourself or read the information and security protocols .... And without taking up space and design: with a depth of only 11 centimetres, the eSanitizer fits into any wall, facilitating access for people and preventing contagion.

PRODUCT SIZES AND PRODUCT VERSIONS

Touch screen:

Fanless Industrial PC:

External connections:

> Power supplies 5/12/24v.

Personalisation/Customisation:

> Airbrushing or multicolour graffiti.

> Industrial paint in various RAL Colours

19" Screen

> UPS 6 sockets/15 min.

> Cut vinyl/digital image.

**Operating System:** 

Electrical panel:

> Atom /Celeron, i3, i5, i7.

Android, Windows or Linux

> RJ45/IEC/ I/O switch /Wifi antenna.

> Terminal, circuit breaker and differential.

Uninterruptible Power Supply System:

OPTIONAL COMPONENTS

> IR 3mm or Capacitive 6mm technology.

STANDARD SPECIFICATIONS

Display:

> Industrial LCD 24/7.

> 19", 16:9 (wide / horizontal)

> Antivandalic glass 3+3 mm.

>1 Door with security lock.

> Internal terminal strip with I/O switch.

Thermal camera

Colour of front: ORAL 9003/9007 plain.

Textured o plain.

Screen resolution:

Number of screens:

> HDMI, DVI, SVGA

Screen protection:

Video output:

Accesses:

Connections:

Structure colour:



### **OPTIONAL ADAPTATIONS**

Screen resolution: > 12,1", 19", 22". Screen layout: > Horizontal or vertical (please consult).

Dispensers: > Electro-Automatic Gel Dispenser (1 litre) with hand proximity sensor. > Glove Dispenser (Bag or Latex).

Thermal camera: > Facial recognition > 8" screen

Customised front with fretwork: > With or without led backlight

### MOST COMMON APPLICATIONS

> Embedded Solutions

- > Information point.
- > Identification.
- > Self-Service Applications > Betting kiosk
- > Access control.

### MOST COMMON SECTORS

- > Tourism, hotels and restaurants.
  > Sports and leisure.
  > Education and health.

- > Logistics and transport.
  > Museums and libraries.
  > Public administration (e-administration, official bodies, corporations).
  > Communication, advertising and marketing.

