

ePanel series

Industrial Monitors

Industrial Components



Elevation

Series of IP65 industrial touch monitors of professional range for outdoor use or sunlight incidence (*). Brightness sensor and **selector for automatic brightness adjustment**. Different sizes from 10.1" to 21.5". Tempered glass hardness 7H, optical bonding and UV protection. 3mm aluminium alloy front bezel, durable and specially designed for panel mounting. **Allows 12v and 36v voltage.**



Rear

TECHNICAL SPECIFICATIONS

Most used sizes:

15" panel [eMonitor TH 15" EXT]

- Native resolution: 1024x768 (4:3)
- Contrast: 1000:1 / Brightness: 1000cd/m2
- Operating Temp.: -20 ~ 70 °C

17" Panel

- Native resolution: 1280x1024 (5:4)
- Contrast: 1000:1 / Brightness: 1000cd/m2
- Operating Temp.: -20 ~ 70 °C

21.5" Panel

- Native resolution: 1920x1080 (16:9)
- Contrast: 1000:1 / Brightness: 1200cd/m2
- Operating Temp.: -20 ~ 70 °C

Other sizes available: 10.1" 1280*800 16:10 / 10.4" 1024*768 4:3 / 11.6" 1920*1080 16:9 / 12" 1024*768 4:3 / 12.1" 1280*800 16:10 / 13.3" 1920*1080 16:9 / 15.6" 1920*1080 16:9 / 18.5" 1920*1080 16:9 / 19" 1280*1024 4:3 / 19.1" 1440*900 16:10. Consult other sizes.

OTHER TECHNICAL DATA

- <Touch interface RJ45 to USB. Standard VGA, DVI and HDMI video input.
- Industrial LCD display with multi-language OSD panel.
- Front bezel housing made of 3mm aluminium alloy, durable and perfect for paneling.
- Multi-point capacitive touch screen.
- Compatible with **Windows, Linux and Android** operating systems.
- Greyscale response time 5ms
- Dot distance: 0.264mm
- Contrast From 800:1 / Brightness 1000cd/m2
- LED backlight type, use length≥50000h Display colour: 16.7 million
- Viewing angle 160/160° (customisable 178° full viewing angle)
- Number of touches ≥ 50 million times
- Power supply 4A. External power adapter
- Power output 100-240V, 50-60HZ
- Input voltage 12-36V. Power ≤48W**
- Antistatic contact 4KV-air 8KV**
- GB2423 anti-vibration standard**
- Anti-EMC interference** EMI anti-electromagnetic interference
- Ambient temperature <80%, non-condensing.
- Working temperature -20°C~70°C
- Audio input and output


I/O PORTS




INSTALLATION METHODS

VESA, 100x100mm
75x75mm

PANEL
MOUNT



DRAWING PANEL 12.0"



PRODUCT FEATURES

- > Touch screen with UV protection.
- > Optical bonding screen effectively prevents the screen from fogging up.
- > The brightness of the display can be adjusted, with automatic sensitivity adjustment and manual adjustment via OSD keys.
- > EMC compliant against electromagnetic interference.
- > Industrial protection and adaptable to harsh environments.

MOST COMMON APPLICATIONS

- > Outdoor interactive kiosks.
- > Self-collection / self-payment terminals.
- > Outdoor advertising and digital signage.
- > Unattended outdoor kiosks.

SECTORS OF APPLICATION

- > Shipbuilding industry: boats, ships, vessels.
- > Automotive industry
- > Transport & Logistics
- > Military
- > Airports
- > Catering
- > Supermarkets
- > Service stations

SOME SUCCESS STORIES

- > Outdoor kiosk assembly.
- > Solutions for military equipment.

ALTERNATIVE REFERENCES

- > eMonitor TH EXT




CERTIFICATIONS

Vibration Protection: IEC 60068-2-64, Random, 5 ~ 500 Hz, 1 hr/axis.
Impact Protection: IEC 60068-2-27, Half sine wave, Lasting for 11ms.
Product Certification: CCC / CE / FCC / EMC / CB / ROHS.




DIMENSIONS


DRAWING PANEL 15"



DRAWING PANEL 17"



DRAWING PANEL 19.1"



DRAWING PANEL 21.5"

